Scope of Approval

TN/AD2000-W0/20519/26

Report No. / Manufacturer No. / Validity remark: 8124816550 / 20519 / 06.2026 - 05.2029

to the Certificate as Material Manufacturer acc. to AD 2000-Merkblatt W 0

Outokumpu Stainless AB, Degerfors Operations

Bruksparken 2, SE-69381 Degerfors, Sweden

Revision status: 00

Hamburg, 28.05.2026

TÜVNORD Digitally signed by Liebscher Anne-Kristin

Certification Body

TÜV NORD Systems GmbH & Co. KG
Große Bahnstraße 31, 22525 Hamburg, Germany
tuev-nord.de | certifications@tuev-nord.de

TÜV®

Scope of Approval

TN/AD2000-W0/20519/26

Report No. / Manufacturer No. / Validity remark: 8124816550 / 20519 / 06.2026 - 05.2029

No.	material designation / product form / specification	dimensions / (unit) weight / heat treatment / delivery condition (EN 10027)	AD 2000	remarks
1.1	Austenitische Stähle / Austenitic Steels / Blech / Plate EN 10028-7 prePMA 1326W342970 rev00	 ≤ 75,0 [mm] / +AT (hot rolled) 1a) 75 ≤ t ≤ 150 [mm] / +AT (hot rolled)	W 2, W 10	1a) Dicke > 75 [mm], prePMA 1326W342970, Anforderung gem. Regelwerk. Thickness > 75 [mm]
1.2	X2CrNiMoCuWN25-7-4 (1.4501) / Blech / Plate EN 10028-7	 ≤ 50 [mm] / +AT (hot rolled) 1b)	W 2, W 10	prePMA 1326W342970 Requirements according to the relevant technical standards
1.3	X2CrNiMoN17-13-5 (1.4439) / Blech / Plate TÜV-Verband-WB 405 2)	 ≤ 70 [mm] / +AT (hot rolled)	W 2, W 10	1b) Fertigungssicherheit gemäß AD 2000-Merkblatt W2 wurde überprüft
1.4	X2CrNiMoN22-5-3 (1.4462 / 2205) / Blech / Plate TÜV-Verband-WB 418, 3), 4) prePMA1326WL068950-7 rev00	 ≤ 50 [mm] / +AT (hot rolled) 50 ≤ t ≤ 100 [mm] / +AT (hot rolled)	W 2, W 10	Production quality acc. to AD 2000-Mbl. W2 has been checked TÜV-Az. 1326WL15510
1.5	X1NiCrMoCuN25-20-5 (1.4539 / 904L) / Blech / Plate TÜV-Verband-WB 421, 5),6) prePMA1326WL068950-6 rev00	 ≤ 50 [mm] / +AT (hot rolled) 50 ≤ t ≤ 150 [mm] / +AT (hot rolled)	W 2, W 10	2) Eignungsfesstellung / Approval of material TÜV NORD file: 0121WP12880 3) TÜV NORD file: 0121W117130

Scope of Approval

TN/AD2000-W0/20519/26

Report No. / Manufacturer No. / Validity remark: 8124816550 / 20519 / 06.2026 - 05.2029

No.	material designation / product form / specification	dimensions / (unit) weight / heat treatment / delivery condition (EN 10027)	AD 2000	remarks
1.6	NiCr21Mo (2.4858 / Alloy 825) / Blech / Plate TÜV-Verband-WB 432/1, 8)	≤ 40 [mm] / + AT (hot rolled)	W 2	4) Entfall des Warmzugversuches gemäss VdTÜV-Werkstoffblatt 418, Abs. 10.1, Zustimmungsschreiben der TÜV NORD Systems, TÜV Az.: 1326W045719, Omission of the hot tensile test according to VdTÜV-Werkstoffblatt 418 sec. 10.1; Letter of agreement of TÜV NORD Systems, TÜV file 1326W045719
1.7	X1CrNiMoCuN20-18-7 (1.4547 / 254 SMO) / Blech / Plate prePMA1326WL068950-3 rev2	≤ 50 [mm] / + AT (hot rolled)	W 2, W 10	
1.8	X2CrNiN23-4 (1.4362 / 2304) / Blech / Plate prePMA1326WL068950-1 rev2	≤ 50 [mm] / + AT (hot rolled)	W 2, W 10	
1.9	X2CrNiMoN27-7-4 (1.4410 / 2507) / Blech / Plate prePMA1326WL068950-4 rev00	≤ 50 [mm] / + AT (hot rolled)	W 2, W 10	5) TÜV NORD file: 0121WP32660
1.10	X1NiCrMoCuN25-20-6 (1.4529) / Blech / Plate TÜV-Verband-WB 502	≤ 50 [mm] / + AT (hot rolled)	W 0, W 2	6) Vormaterial für Rohre / Prematerial for tubes Abnahmeprüfzeugnis 3.1 / Certificate 3.1
1.11	X2CrMnNiN21-5-1 (1.4162 / LDX 2101) prePMA1326WL26740 rev06	≤ 40 [mm] / + AT (hot rolled)	W 0, W 2	Siehe Zustimmungsschreiben TÜV NORD see letter of agreement by TÜV NORD TÜV NORD file 0121WL15590-1
1.12	X2CrNiMnMoCuN24-4-3-2 (1.4662 / LDX 2404) prePMA1326WL50920 rev03	≤ 75 [mm] / + AT (hot rolled)	W 0, W 2	7) UNS S31803 and UNS S32205 <= 75 mm 8) TÜV NORD file 1326W200476

Scope of Approval

TN/AD2000-W0/20519/26

Report No. / Manufacturer No. / Validity remark: 8124816550 / 20519 / 06.2026 - 05.2029

No.	material designation / product form / specification	dimensions / (unit) weight / heat treatment / delivery condition (EN 10027)	AD 2000	remarks
2.1	Austenitische Stähle / Austenitic Steels / Blech / Plate			
	ASME SA-240/SA-240M	≤ 75 [mm] / + AT (hot rolled)		
2.2	Austen.-ferritische Stähle / Austenitic-ferritic steels / Blech / Plate			
	ASME SA-240/SA-240M	≤ 50 [mm] / + AT (hot rolled) 7)		